

- Semi-modular Cable Management
- >85% Efficiency at 230V
- Award-winning, proven quality and reliability

This popular PSU A-80 series of Chieftec is now extended by new models featuring cable management. With many awards granted, these PSUs are perfectly suited for cost aware users, who pay attention to both good price and high efficiency.








Technical data	
Model	A-80 750W
Artikel no.	CTG-750C
EAN code	4710713239388
Weight (without/with package)	2.15kg / 2.55kg
Specification	ATX 12V 2.3
Form factor	PS II
Efficiency	>85%
PFC	Active PFC (0.9) (only 230V)
Fan	120mm silent fan
Dimension (DxWxH)	140mm x 150mm x 87mm
Security	AFC (Automatic Fanspeed Control) OPP (Overload protection) OVP (Overvoltage protection) SCP (Short-circuit protection) SIP (Surge & Inrush Protection) UVP (Undervoltage protection)
Warranty	24 Months

Output data							
A-80 series 750W	AC Input	230V 50Hz 6.3A					
	DC Output	+3.3V	+5V	+ 12V1	+12V2	-12V	+5VSB
	Max. Current	22A	22A	30A	30A	0.3A	2.5A
	Max. Combined Power	130W		675W		3.6W	12.5W
			750W				

* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

	Cabel	Connectors	Length (mm)
	24 PIN	1	450
	8 PIN PCI-E (6+2)	2	450
	8 PIN EPS (4+4)	1	550
	SATA	6	2x 450/150/150
	MOLEX	4	2x 450/150/150
	FLOPPY	2	

Certification



* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.