



MORE INFORMATION



MANUALS



All materials are compatible
with RoHS requirements.




Freezer 4U-M Rev. 2

Multicompatible 4U Single Tower CPU Cooler



4-Pin Connector



Specifications

General Specifications

Compatibility	Intel®: LGA 4189, LGA 4677 AMD®: SP6, sTR5, SP3, TR4, sTRX4, sWRX8 Ampere: LGA4926*
Thermal Compound	ARCTIC MX-6 0.8 g Syringe incl.
Weight	1275 g
Dimensions	124 (L) x 156 (W) x 145 (H) mm
Server Rack Unit	4U & up
Operating Ambient Temperature	0–40 °C

*compatible version and a stand-alone mounting kit are available

Heatsink Specifications

Heat Pipe	Direct Touch, Ø 6 mm x 8
Number of Fins	57
Fin Material	Aluminium

Fan Specifications

Fan	2 x 120 mm PWM Fans
Fan Speed	400–2300 rpm, PWM Controlled
Connector	4-Pin Plug
Cable Length	200 mm
Bearing	Dual Ball Bearing
Noise Level	40 dBA
Air Flow	71.90 cfm 122.16 m ³ /h
Static Pressure	3.30 mmH ₂ O
Current Voltage	0.12 A 12 V DC
Startup Voltage	8 V DC

Shipping Information Freezer 4U-M

Box Dimensions	211 (L) x 160 (W) x 141 (H) mm
Gross Weight	1548 g
SKU	ACFRE00133B
EAN	4895213704960
UPC	840033402637

Shipping Information Freezer 4U-M incl. Ampere Mounting Kit

Box Dimensions	211 (L) x 160 (W) x 141 (H) mm
Gross Weight	1604 g
SKU	ACFRE00171A
EAN	4895265000010
UPC	840033402699

Shipping Information Ampere Mounting Kit

Box Dimensions	160 (L) x 110 (W) x 25 (H) mm
Gross Weight	56 g
SKU	ACOTH00008A
EAN	4895213705042
UPC	840033402644

