



FEATURES

Dissipatore a liquido EVOLIQ 240 V2 ARGB -
240mm, skt universale, PWM, ARGB

SPECIFICATIONS

| | | | |
|-----------------------|------------------------------|-------------------|--|
| TDP | 250W | Operating Voltage | 8~13.2 VDC |
| Radiator Dimension | 274×120×27mm | Started Voltage | 7.5VDC |
| Radiator Material | Aluminum | Rated Current | 0.22~0.39A (Fan Moto)+0.3A (RGB) |
| Tube Material | PTFE tube + Rayon mash cover | Power Input | 4.7W+1.5W |
| Tube Length | 400mm | Bearing Type | Hydraulic Bearing |
| Water block Dimension | 70×80×54.3mm | CPU Compatibility | Intel LGA2066/2011/1700/1200/1150/1151 /1155/1156/775/1366 |
| Cold Plate Material | Oxygen-free Copper | | AMD TR4/ AM5/AM4/FM2+/FM2/FM1/ AM3+/AM3/AM2+/AM2 |
| Pump Current | 0.46A | | |
| Pump Speed | 2600±10% RPM | | |
| Pump Bearing | Ceramic Bearing | | |
| Pump Life Expectancy | 50,000 Hrs. | | |
| Pump Noise Level | 16dB(A) | | |
| RGB Version | AURA 5V 3Pin addressable | | |
| Fan Dimension | 120×120×25mm | | |
| Included Fans | 2pcs | | |
| Fan Speed | 400-1800±10% RPM | | |
| Max. Air Flow | 73.6CFM | | |
| Max. Air Pressure | 2.12mm H2O | | |
| Noise | 8~29.1dB(A) | | |
| Rated Voltage | 12VDC | | |

PACKING INFORMATION

SOCIAL MEDIA COMMUNICATION

Code: ITLCEVOA240V2
EAN: 8056157883241

