PALIT GEFORCE RTX 4080 SUPER





INFINITY 3 OC

Powering Advanced Al

Key Features

NVIDIA

- Dedicated Ray Tracing Cores
- Dedicated Tensor Cores
- NVIDIA DLSS 3
- Game Ready and NVIDIA Studio Drivers

GEFORCE

- NVIDIA® GeForce ExperienceTM
- NVIDIA Broadcast
- **□** NVIDIA G-SYNC®
- NVIDIA GPU BoostTM
- GDDR6X Graphics Memory
- ☐ PCI Express® Gen 4
- Microsoft DirectX® 12 Ultimate
- Vulkan RT APIs, Vulkan 1.3, OpenGL 4.6
- HDCP 2.3
- □ DisplayPort 1.4a, up to 4K at 240Hz or 8K at 60Hz with DSC, HDR
- As specified in HDMI 2.1a: up to 4K 240Hz or 8K 60Hz with DSC, Gaming VRR, HDR

Minimum System Requirements

- PCI Express-compliant motherboard with one tri-width x16 graphics slot
- 850 W or greater system power supply
- ☐ One 16-pin PCle 12VHPWR or two 8-pin supplementary power connectors
- Microsoft Windows® 11, Windows® 10 64-bit, Linux 64-bit

Part Number	NED408SS19T2-1032S
EAN Code	4710562244779
GPU	GeForce RTX 4080 SUPER
CUDA Core	10240
Core Clock	2295 MHz
Boost Clock	2580 MHz
DRAM Type	GDDR6X
DRAM Amount	16 GB
DRAM Interface	256 bits
DRAM Speed	23 Gbps
DRAM Bandwidth	736 GB/s
Board Power	320 W
Output	DP 1.4a x 3 HDMI 2.1a x 1
Bracket	2 slots
Cooler	2.5 slots
Board Size	294 x 116 x 49.5 mm
Box Size	373 x 212 x 97 mm
Retail Pack	10 pcs per carton
Box Including	➢ GeForce RTX 4080 SUPER➢ Power Cable

Product Specifications and Features are for reference only and are subject to change without prior notice.

Build Small. Play Big.

SFF-Ready Enthusiast
GeForce Cards and Cases

SFF-Ready Enthusiast GeForce Cards are RTX 4070 or higher with the following dimensions:

- > 151 mm maximum height including power cable bend radius
- > 304 mm maximum length
- > 50 mm or 2.5 slots maximum depth

