



Enhanced Visual Appeal

Under operation, the F12 Racing ARGB exhibits a concentric circular lighting effect, enhancing the overall visual appeal with its sleek and layered illumination.

Bright ARGB

Full-spectrum ARGB lighting, to meet the individual needs of most players, and you can enjoy a distinctive vision after powering on.

Superior Heat Dissipation

The seven semi-transparent fan blades feature three-dimensional grooves, achieving superior cooling performance.

Hydraulic Bearing Fan

Durable hydraulic bearing with a lifespan of over 40,000 hours.

Quiet & Stable

Equipped with 8 rubber pads, which can greatly reduce operating noise and improve efficiency.

ARGB/PWM Controller




- A** FAN: PWM Port (4pin)
- B** LED: ARGB port (3pin)
- C** DC-IN: SATA Power Connector
- D** LED CTRL: External LED Connector (Connect to the reset button of the chassis to turn it into the LED control)
- E** LED SPEED: Control the speed of lighting effects (Low/Mid/High)
- F** PWM LED: External Signal Connector (Connect to the Motherboard for ARGB & PWM functions)
- G** MODE: Switch the lighting effects

Package



F12 Racing ARGB
Single Pack (No Controller)



F12 Racing ARGB 3 in 1 Pack
With an ARGB & PWM Controller

| Specification | |
|-------------------|--|
| Fan Type | ARGB Fan |
| Dimensions | 120 x 120 x 25 mm |
| Bearing Type | Hydro Bearing |
| Fan Speed | 500±200-1500±10%RPM |
| Airflow | 52.75 CFM |
| Air Pressure | 1.76 mmH ₂ O |
| Fan Noise Level | 28 dB(A) |
| Lifespan | 40,000 hrs 25°C |
| Connector | 4-pin PWM 3-pin ARGB |
| Rated Voltage | FAN: DC 12 V LED: DC 5 V |
| Operation Voltage | FAN: DC6.0-13.8V LED: DC4.5-5.3V |
| Rated Current | FAN: ≤ 0.15 A LED: ≤ 0.288 A |
| Warranty | 1 Year |
| UPC# | 0-761345-40014-5 F12 Racing ARGB 0-761345-77760-5 F12 Racing ARGB_3PK |