

UTA-02

Universal Travel Adapter with
1xUSB-C PD 20W / 1xUSB-A QC 3.0



World-to -World
adapter



1x USB-A QC 3.0 18W



1x USB-C PD 20W



Charge 3
devices at once

Worldwide Travel Adapter

The Verbatim Universal Travel Adapter can be used in more than 180 countries - take it everywhere with you and never be out of power.

This world-to-world multi plug will recharge your power-hungry devices, like laptops and camera batteries, and the USB-C and USB-A ports on the bottom can charge all your USB devices including smartphones, Bluetooth speakers, tablets, power banks, and Kindles.

The compact and powerful Universal Travel Adapter allows 3 devices to be charged simultaneously through the AC power socket and the USB-A and USB-C ports.

UTA-02

Universal Travel Adapter with 1xUSB-C PD 20W / 1xUSB-A QC 3.0

PN	Description	Bar Code	EAN128 Code	EAN14 Code
49544	Verbatim UTA-02 Universal Travel Adapter with 1xUSB-C PD 20W / 1xUSB-A QC 3.0	023942495444	(02)00023942495444(37)20(91)489	50023942495449

General Information			
Input Plug Formats	Type A / B / C / D / E / F / G / H / I / J / K / L / M / N / O		
Output Plug Formats	EU, UK, USA/Japan, AUS/China Type A / B / C / E / F / G / I / J / L / N		
Material	Fire-proof polycarbonate, Copper		
Product Dimensions LxWxH (mm)	65 x 50 x 54	Product Weight (grams) approx	133
Colour	Black	Safety shutter	Yes
Power			
Max Current	10A / 2500W	Voltage range	100-250 V
Working frequency	50-60 Hz	Earthed Plug	No
Fuse	10A, 250V (spare fuse included)	Fuse Compliance	BS1362
USB-A Output	Quick Charge: 5.0V 3.0A 15.0W, 9.0V 2.0A 18.0W, 12.0V 1.5A 18.0W		
USB-C Output	Power Delivery: 5.0V 3.0A 15.0W, 9.0V 2.22A 20.0W, 12.0V 1.67A 20.0W		
Other Features			
Indoor / Outdoor use	Yes / No	LED Indicators	Yes
Protective Functions	Safety shutter for child protection; can only be opened with force of more than 75N (7.5Kg) per hole		
Compliance	EN 55014-1: 2006+A1: 2009+A2: 2011 EN 55014-2: 1997+A1: 2001+A2: 2008 EN 61000-3-2: 2014 EN 61000-3-3: 2013		

Storage and Operating Conditions	
Storage Temperature	-20°C to 85°C
Operating Temperature	0°C to 35°C
Operating Humidity	25% to 90% RH

Logistic Information	
Pack Dimensions LxWxH	90 x 57 x 105 mm
Pack Weight	160 g
Pcs per Pack	1
Outer Cartons Dimensions	310 x 235 x 210 mm
Outer Cartons Weight	3 700 g
Pcs per Outer Carton	20
Outer Carton per Layer	17
Layers per Pallet	6
Pcs per Pallet	2 040

Pack Contents:

- Verbatim UTA-02 Universal Travel Adapter with 1xUSB-C PD 20W / 1xUSB-A QC 3.0
- Quick Start Guide

Warranty

- 2 Year Limited Warranty

Warning

- DOES NOT CONVERT VOLTAGE
- INDOOR USE ONLY

SCAN OR CLICK HERE
FOR MORE INFO:



UTA-02

Universal Travel Adapter with
1xUSB-C PD 20W / 1xUSB-A QC 3.0

Image library

Download high-res images from the
marketing directory:
www.verbatim-marcom.com



Back



Front



Right angled UK plug



Right angled EU plug



Left angled USB



Packaging 3D



Lifestyle 1



Lifestyle 2



Lifestyle 3



Lifestyle 4



Lifestyle 5



Lifestyle 6