

850 W / 750 W / 650 W



SPECIAL FEATURES

- ❖ OptiSink Design
- ❖ ATX 3 and PCIe 5 Compatible
- ❖ High Efficiency, 80 PLUS® Gold Certified
- ❖ Fully Modular Cabling Design
- ❖ Native 12V-2x6 Cable
- ❖ Compact Size (140 mm)
- ❖ Tight Voltage Regulation (12 V, 5 V and 3.3 V) [± 3%]
- ❖ Cable-free Connection Design
- ❖ 7 Years Warranty

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
CORE GX-850	20 A	20 A	70 A	0.3 A	3 A	850 W
			100 W	840 W	3.6 W	
CORE GX-750	20 A	20 A	62 A	0.3 A	3 A	750 W
			100 W	744 W	3.6 W	
CORE GX-650	20 A	20 A	54 A	0.3 A	3 A	650 W
			100 W	648 W	3.6 W	



CONNECTOR QUANTITY

Cable							
	Main Power (24P / 20P) 610 mm	EPS 12V / ATX 12V (8P / 4P) 750 mm	12V-2x6 (12+4P to 12+4P) 700 mm	PCIe (6+2P) 750 mm	PCIe (16P to 2x 6+2P) 700 mm	SATA 750 mm	Peripheral (4P) 690 mm
CORE GX-850	1	2	1	1	1	2	1
CORE GX-750	1	2	1	0	1	2	1
CORE GX-650	1	2	1	0	1	2	1



Certifications:

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 140 mm (L) x 150 mm (W) x 86 mm (H)

Specifications may change without prior notice.



Headquarters sales@seasonic.com
 USA ssa.sales@seasonic.com
 Europe sse.sales@seasonic.com

www.seasonic.com